







## FORMULATOR AND MANUFACTURER

## **SPECGUARD'S PRODUCT FOCUS:**

- Utilizing todays innovative technology
- Ponding water resistance
- Self priming products
- No asphalt bleed through
- High adhesion, high tensile strength
- Flexibility and durability
- System compatibility
- Faster dry times
- Environmentally conscious products
- Maintainable and sustainable systems

## **OUR TECHNOLOGY PARTNERS:**





























## SPECGUARD PRODUCT DESCRIPTIONS

## SPECGUARD SG-54 Modified Acrylic Topcoat / Features: (Ponding water resistant, high adhesion and fast drying)

- High water resistance, holds up under ponding water
- High solid content 20% thicker than standard acrylic coatings
- High adhesion, Priming resins built into the product
- Quick drying, reduces the chance of problems with heavy condensation and light rain
- High UV reflectivity
- No asphalt bleed through

### SPECGUARD SG-40 Modified Acrylic Basecoat / Features: (High adhesion, ponding water resistance and fast drying)

- High water Resistance, holds up under ponding water
- High adhesion, Priming resins built into the product, high adhesion to the existing roof
- Quick drying, reduces the chance of problems with heavy condensation and light rain
- No asphalt bleed through

### SPECGUARD SG-44 Modified Acrylic Topcoat / Features: (Reduces heat transfer, high adhesion and fast drying)

- Cost effective product for higher sloped roofs with good drainage and minimal ponding areas
- Reduce heat transfer into the building, reduces energy cost
- Extends the life span and decrease further wear of an existing roof
- High adhesion, Priming resins built into the product

#### SPECGUARD SG-64 Modified Acrylic alternative to Silicone / Features: (Ponding water resistance, high adhesion)

- Provides the performance of silicone at a more competitive price
- Allows for higher mil thickness system specifications and increased performance at a lower overall cost
- Eliminates the adhesion issues associated with silicones when maintenance is required
- Warranties ponding water areas
- No asphalt bleed through




## **GRANULATED CAP SHEET SYSTEMS**






#### STANDARD 10 YEAR SYSTEM FOR GRANULATED CAP SHEET ROOFS



## OPTIONAL 15 YEAR SYSTEM FOR GRANULATED CAP SHEET ROOFS



### Utilize the **SG40** for all 3 course prep and seams

- PONDING WATER PROTECTION
- **QUICK DRY TIMES**
- COMPLETE PRODUCT COMPATIBILITY

### THE ROOF SURFACE MUST BE CLEAN AND FREE FROM DIRT AND DEBRIS PRIOR TO SYSTEM APPLICATION



# 3 COURSE, ALL PENETRATIONS, EQUIPMENT AND VERTICAL SEAMS WITH SG40 AND POLYESTER FABRIC










# 3 COURSE, DRAINS, SKYLIGHT PERIMETER AND REPAIRED SEAMS WITH SG40 AND POLYESTER FABRIC















APPLY SG40 BASECOAT TO THE ROOF DECK AND OVER THE SEAMS



SG40 BASECOAT APPLIED AT 2.5 GALLONS PER SQUARE OVER THE SEAMS AND THE ENTIRE ROOF DECK





SG40 BASECOAT / SG54 TOPCOAT PROVIDE HIGH ADHESION, HIGH WATER RESISTANCE / SYSTEM COMPATIBILITY



## SPECGUARD FLUID APPLIED COMMERCIAL ROOF SYSTEM

SPECGUARD PRODUCTS AND SYSTEMS UTILIZE TODAYS MOST INNOVATIVE TECHNOLOGIES:

- PONDING WATER RESISTANCE
- NO ASPHALT BLEED THROUGH
- SELF PRIMING SYSTEM
- FASTER DRY TIMES
- HIGH ADHESION, HIGH TENSILE STRENGTH
- HIGH SOLIDS CONTENT

SG-40 MODIFIED ACRYLIC BASECOAT

# COMPLETED SPECGUARD SG40 BASECOAT / SG54 TOPCOAT FLUID APPLIED ROOF SYSTEM



# specguard



#### **SPECGUARD COATING SYSTEMS**

909 Mahar Ave, Wilmington, CA 90744

Website: www.specguard.us.com

**E-mail:** sales@specguard.us.com / **Direct:** 310-722-7516 / **Office:** 310-834-7037















