

SPECGUARD POLYESTER FABRIC

Specguard Polyester fabric is one of the strongest materials available to the roofing industry for use as reinforcement in roofs and decks. Polyester roofing fabric offers an unusual combination of high strength properties with good elongation for excellent thermal stress force accommodations. Specguard Polyester fabric is a soft polyester that will readily conform to, irregular, and smooth surfaces, roof equipment, roof penetrations and roof decks.

AVERAGE TYPICAL PROPERTIES:

Specifications	
Material	Polyester
Weight	N/A 3-oz/sq yd
Tensile	ASTM D 1682 57.1 lbs*
Elongation	ASTM D 1682 61.65%*
Mullen Burst	ASTM D 3786 176.8 lbs
Trapezoid Tear Strength	ASTM D 1117 16.1 lbs



PACKAGING:

Polyester Fabric are packaged as follows

40-inches wide x 275 feet long, with lap lines for one and two ply application.

5-inch wide x 275' feet long

8-inch wide x 275' feet long,

10-inch wide x 275' feet long,

Disclaimer: Specguard assumes no responsibility for the use of information presented herein and hereby expressly disclaims all liability in regard to such use. Design, Examination or Inspection: Specguard does not practice engineering or architecture. Therefore, Specguard cannot and does not warrant any review of construction or design plans or applications. The owner is encouraged to retain its own inspectors, engineer, architect and/or other professionals to review any and all designs or modifications.

SPECGUARD SYSTEMS

909 Mahar Ave, Wilmington, CA 90744

Website: www.specguard.us.com / **E-mail:** sales@specguard.us.com / **Phone:** 310-834-7037